


# Olodum Standard Tondo COB



IK 10  
IP 67




Velocità max carrabilità 20 km-h    Carico statico 2000 kg  
Drive-over max speed 20 km-h    Static load 2000 kg


- Corpo in pressofusione di alluminio, verniciato in polveri con pretrattamento speciale per esterni.
- Anello di finitura in acciaio Inox (AISI 316).
- Pressacavo in ottone nichelato PG13,5.
- Vetro temperato di spessore 10 mm.
- Body in die-cast aluminium with special powder treatment for outdoor use.
- Stainless steel (AISI 316) frame.
- PG13,5 nickel brass cable gland.
- Tempered glass 10 mm thick.
- 50,000 rated average design life\*



| LED COB                                    | W   | lm   | V        | K    | T   | • | • |
|--|-----|------|----------|------|-----|---|---|
| <b>LUCE SIMMETRICA - SYMMETRIC LIGHT</b>   |     |      |          |      |     |   |   |
| Inox E8128-LBC-S SPOT                      | 18W | 2600 | 220-240V | 3000 | 65° | • | • |
| Inox E8128-LBC-FL FLOOD                    |     |      |          |      |     |   |   |
| Inox E8128-LBC-WF WIDE FLOOD               |     |      |          |      |     |   |   |
| <b>LUCE ASIMMETRICA - ASYMMETRIC LIGHT</b> |     |      |          |      |     |   |   |
| Inox E8128-LBN-S SPOT                      | 18W | 2700 | 220-240V | 4000 | 65° | • | • |
| Inox E8128-LBN-FL FLOOD                    |     |      |          |      |     |   |   |
| Inox E8128-LBN-WF WIDE FLOOD               |     |      |          |      |     |   |   |
| <b>LUCE ASIMMETRICA - ASYMMETRIC LIGHT</b> |     |      |          |      |     |   |   |
| Inox E8128-LBC-AS                          | 18W | 2300 | 220-240V | 3000 | 55° | • | • |
| Inox E8128-LBN-AS                          |     | 2500 |          | 4000 |     |   |   |



| LED COB                                    | W   | lm   | V        | K    | T   | • | • |
|--|-----|------|----------|------|-----|---|---|
| <b>LUCE SIMMETRICA - SYMMETRIC LIGHT</b>   |     |      |          |      |     |   |   |
| Inox E8131T-LBC-S SPOT                     | 18W | 2600 | 220-240V | 3000 | 65° | • | • |
| Inox E8131T-LBC-FL FLOOD                   |     |      |          |      |     |   |   |
| Inox E8131T-LBC-WF WIDE FLOOD              |     |      |          |      |     |   |   |
| <b>LUCE ASIMMETRICA - ASYMMETRIC LIGHT</b> |     |      |          |      |     |   |   |
| Inox E8131T-LBN-S SPOT                     | 18W | 2700 | 220-240V | 4000 | 65° | • | • |
| Inox E8131T-LBN-FL FLOOD                   |     |      |          |      |     |   |   |
| Inox E8131T-LBN-WF WIDE FLOOD              |     |      |          |      |     |   |   |
| <b>LUCE ASIMMETRICA - ASYMMETRIC LIGHT</b> |     |      |          |      |     |   |   |
| Inox E8131T-LBC-AS                         | 18W | 2300 | 220-240V | 3000 | 55° | • | • |
| Inox E8131T-LBN-AS                         |     | 2500 |          | 4000 |     |   |   |



OP. ...-TSC TORX Viti di sicurezza - Safety screws

ACC. 645230 Connettore IP68 Ø da 7 a 10mm - IP68 connector Ø from 7 to 10mm

E960 Ventosa per rimuovere vetro - Glass remover

Griglia alveolare - Honeycomb



3 year warranty

\*Rated average design life is in accordance with IEC standards. Actual product life may vary dependent upon frequency of maintenance and product application.