

PERFECT LUMINAIRE SOLUTION



ORION ECO LED OYSTER

Introducing new generation of the PIERLITE Orion ECO LED Oyster, perfect luminaire solution for surface mounting in residential and commercial interior spaces, where there is limited space in the ceiling or there are concrete ceilings.

Orion ECO LED OYSTER

PIERLITE Orion ECO LED Oyster now available in 3 popular sizes and wattages along with three colour temperatures of warm white, cool white and day light for different application requirements including residential, commercial and retail spaces. Opalised acrylic diffuser provides a uniform lit appearance, while integral driver together with twist and lock diffuser ensure ease of installation.

FEATURES

- Powder coated white steel base
- Low glare opal PMMA diffuser
- White removable trim to enhance the appearance
- IP44 rating reduces foreign bodies entering the unit
- Up to 95lm/W
- Available in 3000K, 4000K and 6500K
- Rated average design life 25,000 hrs

BENEFITS

- Excellent and even light distribution
- Easy to install with quick fit twist front diffuser and an integral control gear
- More flexibility with 3 different wattages, sizes and 3 colour temperature options

SPECIFICATIONS

- IP44
- Ta25
- Voltage: 240V
- CRI>80
- Available in 3 sizes & 3 colour temperatures
 10W Ø250mm: 3000K, 740lm; 4000K, 800lm; 6500K, 845lm
 16W Ø300mm: 3000K, 1160lm; 4000K, 1230lm; 6500K, 1250lm
 23W Ø350mm: 3000K, 2000lm; 4000K, 2160lm; 6500K, 2225lm
- Non Dimmable

APPLICATIONS

Resident, commercial or retail applications

PRODUCT CODE	DESCRIPTION	WATTAGE	LUMEN	COLOUR TEMP	DIMMENSION (MM)	MASS (KG)	DIMMABLE
ORN10WK3	ORIONMK2 250MM	10W	740lm	3000K	Ø250 x 80.5	0.378	No
ORN10W4K	ORIONMK2 250MM	10W	800lm	4000K	Ø250 x 80.5	0.378	No
ORN10W65K	ORIONMK2 250MM	10W	845lm	6500K	Ø250 x 80.5	0.378	No
ORN16W3K	ORIONMK2 300MM	16W	1160lm	3000K	Ø300 x 80.5	0.546	No
ORN16W4K	ORIONMK2 300MM	16W	1230lm	4000K	Ø300 x 80.5	0.546	No
ORN16W65K	ORIONMK2 300MM	16W	1250lm	6500K	Ø300 x 80.5	0.546	No
ORN23W3K	ORIONMK2 350MM	23W	2000lm	3000K	Ø350 x 81	0.615	No
ORN23W4K	ORIONMK2 350MM	23W	2160lm	4000K	Ø350 x 81	0.615	No
ORN23W65K	ORIONMK2 350MM	23W	2225lm	6500K	Ø350 x 81	0.615	No



*Rated average design life is based on application of PIERLITE's product operating and maintenance guidelines; see www.gerardlighting.com.au. Actual product life may vary dependent upon frequency of maintenance and product application.



Issue: April 2017



PIERLITE is a registered trademark of Gerard Lighting Pty Ltd ©Copyright PIERLITE 2017 gerardlighting.com.au

