

# Fusion T5

Energy efficient T5 recessed troffer, suitable for an array of diffuser panels enabling BCA compliant designs.

## Specification

- Body of steel with highly reflective powder coat finish
- Suitable for lay in or hinged frame diffuser panels
- Available with high performance panels Y19 and Y12, refer version listed below Recess
- depth of 85mm providing low glare illumination in accordance with AS1680.1
- Available DALI dimming
- Suitable for use with Plaster Master frame for plaster mounting
- Suitable for air trim kits
- Product codes listed below are for lay in diffuser

## Product Codes

Code	Version	Dim (mm)	Mass (kg)
FSN214P2A4	2x14W Y12 Lay panel 4K	594 x 294 x 85	4.4
FSN228P9A4	2x28W Y19 Lay panel, EL 4k	1194 x 294 x 85	4.4
FSN228P2A4	2x28W Y12 Lay panel, EL 4K	1194 x 294 x 85	4.8
FSN228P9A4	2x28W Y19 Lay panel, EL 4K	1194 x 294 x 85	4.8






## Quick Specification

Pierlite recessed T5 4K, diffused, lay in or hinged frame, shallow depth, low glare system

## Design Application

Retail shops, office, corridors, boardrooms, common area, canteens, foyers, halls, auditoriums, hospitals, shopping centres.

## Performance



IP20



Max Dim (mm)  
1194 x 294 x 85

PDF Prepared: 25.09.2017 16:09pm, Last page update: Jul 2017



**PIERLITE**  
professional lighting solutions