



## CILINDRO 108

### *LED Track Spot Light Range*

Cilindro is an innovative family of LED track spot lights, which offer the designer a range of lumen outputs, beam angles and colour temperatures. With its simple discrete design, the Cilindro integrates into the environment, while its efficient AC LED module makes this family the perfect alternative to conventional lighting sources.



# CILINDRO 108

## LED Track Spot Light Range



### Features

- Diecast body with a drop forge heatsink
- Interchangeable optics, outputs and styles 12°/24°/ 40°, standard 24°
- Citizen CL Series AC LED @ 85CRI
- Range available in two sizes and 3 wattages
- Available in 3000K & 4000K colour temperature
- 101 lumens p/w
- Bidirectional adjustment

- Lamp life 50000hrs / 70%
- Compatible with Concord 3C, Staff 3C, Eutrack 3C, Erco 3C, Global 3C, Ivela 3C, Euro Track 3C
- Dimmable using leading edge dimmer. For best performance we recommend use with Diginet LEDsmart+ Dimmers.

### Applications

- Designed for retail fit out, commercial areas, transit corridors, break out areas, lobby's, common areas

### Specifications

Colour Temp	3000K and 4000K
Lumen Output	2842lm
CRI	>85
Macadams Step	3 SDCM
Beam Distribution	Symmetric
Default Beam Angle	24°
Lumen Maintenance	L70 50,000hrs
Control	AC LED
Dimensions	Ø100 x L:139 xH:163
Mounting	3C Universal Track Adaptor
Power Factor	0.9
Electrical Rating	Class I

### Option

Product Code	Description
VA108RS12	CILINDRO 108 - 12° Reflector
VA108RM40	CILINDRO 108 - 40° Reflector

# CILINDRO 108

## LED Track Spot Light Range

### Technical Requirements

Body Selection	Description	Colour Temp	mA Factory Default Setting	Lumens Initial	Lumens Exit	Wattage	CRI	Life / L70	Track Compatability
CI1083AC130	CILINDRO108 30W L3 3K 24D RF WHITE	3000K	AC	3007	2842	30	>85	50,000	Concord 3C Staff 3C Erco 3C Nordic 3C Eutrack 3C Global 3C Ivela 3C
CI1083AC230	CILINDRO108 30W L3 3K 24D RF BLACK	3000K	AC	3007	2842	30	>85	50,000	
CI1083AC330	CILINDRO108 30W L3 3K 24D RF SILVER	3000K	AC	3007	2842	30	>85	50,000	

