



Cellite Armour



Impact resistant surface mount LED luminaire, suitable for use in Correctional Facilities, holding cells, high security areas and areas prone to vandalism. NOTE: For specification/purchase enquiries, please contact GLG as minimum order quantities apply.

- Heavy gauge steel, powder coated white body
- Highly impact-resistant lens
- For internal use only
- Rated IK10
- 52W LED fi. ing
- 50,000 hours rated average life
- 4000K Colour Temperature
- Surface mounted



GENERAL SPECIFICATION

ITEM CODE	DESCRIPTION	WATTAGE	LUMEN OUTPUT	COLOUR TEMPERATURE	CRI
AMRLED52PR0159A	ARMOUR LED 1200MM 52W 4000K	52W	4680Lm	4000K	80

DIMMABLE	DIMMING TECHNOLOGY	IP RATING	IK RATING	FINISH	COLOUR	WEIGHT
No	Non - Dimmable	IP40	IK10	Powdercoated	White	7.9kg

VOLTAGE	DIMENSIONS H x W x L (MM)	CIRCUIT WATTAGE	CHIP CONFIGURATION	LAMP TYPE	OPERATING TEMPERATURE
240V	90 x 242 x 1298	52W	PCB	LED (PCBA)	0 to 40°C

PRODUCT IMAGES

