



Cellite Raw

The Raw is recessed product with wider aperture for improved performance, featuring a white powdercoated heavy-gauge steel body and trim making it ideal for correctional facilities, holding cells and other high security areas. NOTE: For specification/purchase enquiries, please contact GLG as minimum order quantities apply.

- Security recessed LED luminaire for plaster and concrete installations
- 6mm sealed clear polycarbonate lens with PMMA opalized inner
- Rated IK10
- Plaster brackets available for plaster installations
- White powder coated, heavy duty steel frame
- 3000K & 4000K colour temperature
- Security torx screws
- CEL-Skin available for pre-cast concrete mounting



GENERAL SPECIFICATION

CRI	DIMMABLE	DIMMING TECHNOLOGY	IP RATING	IK RATING	FINISH	COLOUR
80	No	Non - Dimmable	IP44	IK10	Powdercoated	White
CUTOUT (MM)	WEIGHT	VOLTAGE	DIMENSIONS H x W x L (MM)	CHIP CONFIGURATION	LAMP TYPE	OPERATING TEMPERATURE
310	13.5kg	240V	100 x 341 x 1316	PCB	LED (PCBA)	0 to 40°C

UNIQUE SPECIFICATION

ITEM CODE	DESCRIPTION	WATTAGE	LUMEN OUTPUT	COLOUR TEMPERATURE	CIRCUIT WATTAGE
CRWLC123E1ENC	CRW LED 27W 3562LM 3K 3W CTR N/L TORX SKB	27W	3562Lm	3000K	27W
CRWLC123P2ENC	CRW LED 48W 6399LM 3K 3W CTR N/L TORX SKB	48W	6399Lm	3000K	48W
CRWLC124E1ENC	CRW LED 27W 3562LM 4K 3W CTR N/L TORX SKB	27W	3562Lm	4000K	27W




Cellite Raw

PRODUCT IMAGES



PHOTOMETRICS



Maximum Candela = 1402.6 Located At Horizontal Angle = 20, Vertical Angle = 1
1 - Vertical Plane Through Horizontal Angles (20 - 200) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (1) (Through Max. Cd.)

CRWLC124E1ENC