

## New Green M



- Corpo e telaio in pressofusione di alluminio verniciato, con polveri poliestere con pretrattamento speciale per esterni.
  - Fissaggio telaio tramite molle (a richiesta viti antivandalo).
  - Vetro di protezione extrachiaro per telaio asimmetrico.
  - Vetro di protezione bianco opalino per telaio simmetrico.
- Aluminum die-cast body and frame painted with polyester powder with pretreatment for outdoor use.
  - Springs fixing frame (on request vandal-proof screws).
  - Transparent extra light protection glass for asymmetrical frame.
  - White opal protection glass for symmetrical frame.
  - 50,000 rated average design life\*



		W	lm	V	K
	<b>LUCE ASIMMETRICA - ASYMMETRIC LIGHT</b>				
	Br E5881-LBC				
	Ne E5882-LBC	5W	450	220-240V	3000
	Ga E5883-LBC				
	Br E5881-LBN	5W	450	220-240V	4000
	Ne E5882-LBN				
	<b>LUCE SIMMETRICA - SYMMETRIC LIGHT</b>				
	Br E5884-LBC				
	Ne E5885-LBC	5W	450	220-240V	3000
	Ga E5886-LBC				
	Br E5884-LBN	5W	450	220-240V	4000
	Ne E5885-LBN				
	<b>OP.</b> A richiesta: versione con viti antivandalo Es. codice ...-V On request: vandal-proof screws version: Ex. code ...-V				
	<b>ACC.</b> 320001 Scatola da immurare Container for recessed wall light 215x85 mm				

3 year warranty

\*Rated average design life is in accordance with IEC standards. Actual product life may vary dependent upon frequency of maintenance and product application.