

New Green XS




- Corpo e telaio in pressofusione di alluminio verniciato con polveri poliestere con pretrattamento speciale per esterni.
- Modulo da incasso a muro per scatole elettriche tipo 503E + 503ESE entrambe in dotazione.
- Fissaggio telaio tramite molle (a richiesta viti antivandalo).
- Guarnizioni e pressacavo in gomma siliconica.
- Vetro di protezione extrachiario per versione asimmetrica.
- Diffusore in policarbonato satinato per versione simmetrica.
- Alimentatore integrato.


- Aluminum die cast body and frame painted with polyester powder with pretreatment for outdoor use.
- Supplied recess wall module for electrical boxes type 503E + 503ESE.
- Springs fixing frame (on request vandal-proof screws).
- Silicon rubber seals and cable gland.
- Transparent extra light protection glass for asymmetrical frame.
- White opal polycarbonate diffuser for symmetrical frame.
- Integrated driver.
- 50,000 rated average design life*



		W	lm	V	K
	LUCE ASIMMETRICA - ASYMMETRIC LIGHT				
	Br E5887-LBC				
	Ne E5888-LBC	4,5W	350	220-240V	3000
	Ga E5889-LBC				
	Br E5887-LBN	4,5W	350	220-240V	4000
	Ne E5888-LBN				
Ga E5889-LBN					
	LUCE SIMMETRICA - SYMMETRIC LIGHT				
	Br E5890-LBC				
	Ne E5891-LBC	4,5W	350	220-240V	3000
	Ga E5892-LBC				
	Br E5890-LBN	4,5W	350	220-240V	4000
	Ne E5891-LBN				
Ga E5892-LBN					



OP. A richiesta: versione con viti antivandalo Es. codice ...-V
On request: vandal-proof screws version: Ex. code ...-V



3 year warranty

*Rated average design life is in accordance with IEC standards. Actual product life may vary dependent upon frequency of maintenance and product application.