



AKA MAJOR

Adjustable LED Downlights Range

AKA blends a mixture of powerful performance with minimalist form critical for harmony within the installed display area. The combination of the “smooth and easy” rotational control is coupled with a constant “clutch” mechanism working in harmony to constantly maintain the optimal tilted position.

AKA MAJOR

Adjustable LED Downlights Range



Features

- Minimalist profile
- Multidirectional 355° rotation 70° tilt
- Flexibility in design and application
- Constant “clutch” tilt mechanism – remains fixed and droop free but easily adjusted
- Heavy duty mounting springs
- 2 fixed driver outputs
- Dimmable – Dali, 1-10v
- High performance optics reflectors with soft edge illumination & 3 beam choices, 20° 40° & 60°
- Accessories for additional light control
- Low glare
- Protective glass front
- 3000k & 4000k with CRI ≥ 90
- Energy efficient replacement to HID

Applications

- Designed for retail, food preparation and facade

Specifications

	Single
Colour temp	3000K and 4000k
Lumen output	See chart
CRI	>90
Macadams step	3 SDCM
Beam distribution	Symmetric
Default beam angle	20°, 40°, 60°
Lumen maintenance	L70 50,000hrs
Control	Remote
Dimensions	Ø186 x H:156mm
Cutout	Ø175mm
Min recessed depth	191mm
Power factor	
Electrical rating	Class III

AKA MAJOR

Adjustable LED Downlights Range

Technical Requirements

40/55W	Required Component		
	Driver		55W
	DAT65F14001	Non-Dim	1400mA*
	DAT55D14001	DALI	
	DAM60V14001	1-10V	
* = Factory Default			

Body selection	Description	Wattage	Lumens Initial	Lumens Exit	mA Setting	Beam Angle	Finishes
AK186314201	AKA MAJOR 55W 3000K 20° REF WHITE	55W	4767	3658	1400mA	20°	Matte White Matte Black Matte Silver
AK186414201	AKA MAJOR 55W 4000K 20° REF WHITE	55W	5132	3979	1400mA	20°	
AK186314202	AKA MAJOR 55W 3000K 20° REF BLACK	55W	4767	3658	1400mA	20°	
AK186414202	AKA MAJOR 55W 4000K 20° REF BLACK	55W	5132	3979	1400mA	20°	
AK186314203	AKA MAJOR 55W 3000K 20° REF SILVER	55W	4767	3658	1400mA	20°	
AK186414203	AKA MAJOR 55W 4000K 20° REF SILVER	55W	5132	3979	1400mA	20°	
AK186314401	AKA MAJOR 55W 3000K 40° REF WHITE	55W	4767	3658	1400mA	40°	
AK186414401	AKA MAJOR 55W 4000K 40° REF WHITE	55W	5132	3979	1400mA	40°	
AK186314402	AKA MAJOR 55W 3000K 40° REF BLACK	55W	4767	3658	1400mA	40°	
AK186414402	AKA MAJOR 55W 4000K 40° REF BLACK	55W	5132	3979	1400mA	40°	
AK186314403	AKA MAJOR 55W 3000K 40° REF SILVER	55W	4767	3658	1400mA	40°	
AK186414403	AKA MAJOR 55W 4000K 40° REF SILVER	55W	5132	3979	1400mA	40°	
AK186314601	AKA MAJOR 55W 3000K 60° REF WHITE	55W	4767	3658	1400mA	60°	
AK186414601	AKA MAJOR 55W 4000K 60° REF WHITE	55W	5132	3979	1400mA	60°	
AK186314602	AKA MAJOR 55W 3000K 60° REF BLACK	55W	4767	3658	1400mA	60°	
AK186414602	AKA MAJOR 55W 4000K 60° REF BLACK	55W	5132	3979	1400mA	60°	
AK186314603	AKA MAJOR 55W 3000K 60° REF SILVER	55W	4767	3658	1400mA	60°	
AK186414603	AKA MAJOR 55W 4000K 60° REF SILVER	55W	5132	3979	1400mA	60°	

AKA MAJOR

Adjustable LED Downlights Range

Technical Requirements

