



Innovative tunable LED technology, progressive optics and state-of-the-art design: Scriptus is specifically developed for illuminating contemporary office environments, and with its innovative technology and functional design sets new standards for today's office lighting. The new multi-level optical system guarantees crisp-edged visual comfort. Separately controllable light components ensure users a high level of individuality for personal settings as well as maximum visual comfort.

Surface-mounting and suspended mounting options.

Optimum glare control: UGR \leq 16 (suspended)

Tunable White for Human Centric functionality.

Direct/Indirect suspended or direct surface mounting

High efficiency of up to 135 lm/W

Rated service life L90 @ 50,000h , Dali 8 standard, IP20

Colour temperature 3000k-6500k for tunable white (mono colour 3k or 4k on request)

Wire suspension to be ordered separately

Product Specification

50000 Rated Average Life	IP20 IP Rating	240V Voltage	80 Color Rendering Index	White Luminaire Colour
Powdercoated Finish	LED (PCBA) Lamp Type	LED Lamp Style	Symmetric Beam Distribution	DALI Dimming Technology

Item Code	Description	Installation Type	Mass (kg)	System Power (W)
5MZ212D0TWA	SCRIPTUS LINEAR S/MNT 1768MM SYMM 37W 4750LM DALI TUNABLE	Surface Mount	6.1KG	37W
5MZ213D0TWA	SCRIPTUS LINEAR S/MNT 2648MM SYMM 53W 7100LM DALI TUNABLE	Surface Mount	7.6KG	53W
5MZ214D0TWA	SCRIPTUS LINEAR S/MNT 3088MM SYMM 53W 7190LM DALI TUNABLE	Surface Mount	9.8KG	53W
5MZ312D0TWB	SCRIPTUS LINEAR SUSP 1768MM SYMM 96W 11150LM DALI TUNABLE	Suspended	6.6KG	96W
5MZ313D0TWB	SCRIPTUS LINEAR SUSP 2648MM SYMM 110W 13880LM DALI TUNABLE	Suspended	8.2KG	110W
5MZ314D0TWB	SCRIPTUS LINEAR SUSP 3088MM SYMM 110W 13970LM DALI TUNABLE	Suspended	10.4KG	110W

Item Code	Lumens per Watt	Lumen Output
5MZ212D0TWA	129	4750Lm
5MZ213D0TWA	134	7100Lm
5MZ214D0TWA	137	7190Lm
5MZ312D0TWB	116	11150Lm
5MZ313D0TWB	126	13880Lm
5MZ314D0TWB	128	13970Lm

SCRIPTUS LED MODULAR SYSTEM

LINE DRAWINGS

