

OLODUM STANDARD LED

COD: E8126-LBC-24

Use:
Outside, led
Installation:
Free standing
Body/structure:
EN AB-47100 Die cast aluminium body. Stainless steel ring and PVC housing

Coating:
Polyester powder coating with special treatment for outdoor use (sandblasting, pickling, n.3 washings, epoxy powder coating and surface finish in polyester powder).



Colour:
Satin stainless steel
Optic/reflector:
Adjustable optic +/- 15° - Metacrylate LED lens

Equipment:
Silicon rubber gaskets
Glass/diffuser:
Clear tempered glass

Gland:
n.2 nichel plated brass cable gland PG13,5
Control gear:
Integrated LED diodes ballast, stabilized output current 700mA dc

Voltage: 220-240V 50/60Hz
Beam: Symmetric narrow beam 24°
Insulation class: Insulation class 1
IP rating: 67
Glow wire: 850 °C
IK rating: 10
TO TRAFFIC: Yes
Static load: 2000 Kg
Roll-over: Yes
Velocita' massima: 20 km/h
Glass temperature: 65 degrees C
Lamp included: YES
LED Type: COB LED
Luminaire wattage: 29.9 W
Luminaire luminous flux: 2126 lm
LED rated life: 50000 hours L80 B20
Colour temperature: 3000K
CRI: 80
Chromacy constancy: 3 SDCM

Review board: 2018-08-01



LAMP: 1 x LED 25.9 W 2760 lm



IK 10 IP 67 A+ RG0

