

## New Green M



- Corpo e telaio in pressofusione di alluminio verniciato, con polveri poliestere con pretrattamento speciale per esterni.
- Fissaggio telaio tramite molle (a richiesta viti antivandalo).
- Vetro di protezione extrachiaro per telaio asimmetrico.
- Vetro di protezione bianco opalino per telaio simmetrico.

- Aluminum die-cast body and frame painted with polyester powder with pretreatment for outdoor use.
- Springs fixing frame (on request vandal-proof screws).
- Transparent extra light protection glass for asymmetrical frame.
- White opal protection glass for symmetrical frame.
- 50,000 rated average design life\*



		W	lm	V	K
<b>LUCE ASIMMETRICA - ASYMMETRIC LIGHT</b>					
	Br E5881-LBC				
	Ne E5882-LBC	5W	450	220-240V	3000
	Ga E5883-LBC				
	Br E5881-LBN				
	Ne E5882-LBN	5W	450	220-240V	4000
	Ga E5883-LBN				
<b>LUCE SIMMETRICA - SYMMETRIC LIGHT</b>					
	Br E5884-LBC				
	Ne E5885-LBC	5W	450	220-240V	3000
	Ga E5886-LBC				
	Br E5884-LBN				
	Ne E5885-LBN	5W	450	220-240V	4000
	Ga E5886-LBN				
	OP.	A richiesta: versione con viti antivandalo Es. codice ...-V On request: vandal-proof screws version: Ex. code ...-V			
	ACC.	320001	Scatola da immurare Container for recessed wall light		
			215x85 mm		

5 year warranty

\*Rated average design life is in accordance with IEC standards. Actual product life may vary dependent upon frequency of maintenance and product application.