


## New Green XL







IP 65  
IK 07




- Corpo e telaio in pressofusione di alluminio verniciato con polveri poliestere con pretrattamento speciale per esterni.
- Fissaggio telaio tramite molle (a richiesta viti antivandalo).
- Vetro di protezione extrachiario per telaio asimmetrico.
- Vetro di protezione bianco opalino per telaio simmetrico.
- Aluminum die-cast body and frame painted with polyester powder with pretreatment for outdoor use.
- Springs fixing frame (on request vandal-proof screws).
- Transparent extra light protection glass for asymmetrical frame.
- White opal protection glass for symmetrical frame.
- 50,000 rated average design life\*




		Ⓜ	lm	V	K
	LUCE ASIMMETRICA - ASYMMETRIC LIGHT				
	Br E5875-LBC				
	Ne E5876-LBC	8,5W	910	220-240V	3000
	Ga E5877-LBC				
	LUCE SIMMETRICA - SYMMETRIC LIGHT				
	Br E5878-LBC				
	Ne E5879-LBC	8,5W	910	220-240V	3000
	Ga E5880-LBC				
	LUCE ASIMMETRICA - ASYMMETRIC LIGHT				
	Br E5875-LBN				
	Ne E5876-LBN	8,5W	910	220-240V	4000
	Ga E5877-LBN				
	LUCE SIMMETRICA - SYMMETRIC LIGHT				
	Br E5878-LBN				
	Ne E5879-LBN	8,5W	910	220-240V	4000
	Ga E5880-LBN				

OP. A richiesta: versione con viti antivandalo Es. codice ...-V  
On request: vandal-proof screws version: Ex. code ...-V



ACC. 320000 Scatola da immergere  
Container for recessed wall light

355x85 mm



5 year warranty

\*Rated average design life is in accordance with IEC standards. Actual product life may vary dependent upon frequency of maintenance and product application.