


New Green XS



IP 65
IK 07




- Corpo e telaio in pressofusione di alluminio verniciato con polveri poliestere con pretrattamento speciale per esterni.
- Modulo da incasso a muro per scatole elettriche tipo 503E + 503ESE entrambe in dotazione.
- Fissaggio telaio tramite molle (a richiesta viti antivandalo).
- Guarnizioni e pressacavo in gomma siliconica.
- Vetro di protezione extrachiario per versione asimmetrica.
- Diffusore in policarbonato satinato per versione simmetrica.
- Alimentatore integrato.




- Aluminum die cast body and frame painted with polyester powder with pretreatment for outdoor use.
- Supplied recess wall module for electrical boxes type 503E + 503ESE.
- Springs fixing frame (on request vandal-proof screws).
- Silicon rubber seals and cable gland.
- Transparent extra light protection glass for asymmetrical frame.
- White opal polycarbonate diffuser for symmetrical frame.
- Integrated driver.
- 50,000 rated average design life*

			(W)	(lm)	(V)	(K)
	LUCE ASIMMETRICA - ASYMMETRIC LIGHT					
	Br	E5887-LBC				
	Ne	E5888-LBC	4,5W	350	220-240V	3000
	Ga	E5889-LBC				
	Br	E5887-LBN				
	Ne	E5888-LBN	4,5W	350	220-240V	4000
	Ga	E5889-LBN				
	LUCE SIMMETRICA - SYMMETRIC LIGHT					
	Br	E5890-LBC				
	Ne	E5891-LBC	4,5W	350	220-240V	3000
	Ga	E5892-LBC				
	Br	E5890-LBN				
	Ne	E5891-LBN	4,5W	350	220-240V	4000
	Ga	E5892-LBN				



OP. A richiesta: versione con viti antivandalo Es. codice ...-V
On request: vandal-proof screws version: Ex. code ...-V



5 year warranty

*Rated average design life is in accordance with IEC standards. Actual product life may vary dependent upon frequency of maintenance and product application.